

Datto SIRIS 5 NVMe SSD Models

datto | UNIFIED CONTINUITY

Hardware Specifications

Model	S5-SSD-10	S5-SSD-30
Capacity (TB)	10	30
Drives	4x 3.84TB	10x 3.84TB
Storage array	RAID 5	RAID 6
Storage type	Enterprise NVMe U.2 Gen4	Enterprise NVMe U.2 Gen4
OS drive	2x 240GB m.2 RAID-1 on BOSS card	2x 240GB m.2 RAID-1 on BOSS card
SLOG drive	Not required	Not required
CPU(s)	2x Xeon Silver 4210 2.2G, 10C/20T	2x Xeon Gold 5218R 2.1G 20C/40T
RAM	96GB DDR4 ECC (6x 16)	192GB DDR4 ECC (12x 16)
LAN ports	2x 10Gb Base-T + 2x 1Gb Base-T	2x 10Gb Base-T + 2x 1Gb Base-T
Video	VGA	VGA
Remote management	IPMI / iDRAC Enterprise	IPMI / iDRAC Enterprise
Power supply	Dual, redundant 750W	Dual, redundant 750W
Input voltage	120 – 240 V	120 – 240 V
Form factor	1U rackmount full-depth	1U rackmount full-depth
Weight	48.3lbs / 21.9kg	48.3lbs / 21.9kg
Dimensions (with bezel for rackmount)	1.69 x 18.98 x 31.8" 4.28 x 48.2 x 80.9cm	1.69 x 18.98 x 31.8" 4.28 x 48.2 x 80.9cm
Maximum heat dissipation	1,228 BTU/hr	1,856 BTU/hr
Datto limited warranty	Lifetime	Lifetime



datto
A Kaseya COMPANY

Corporate Headquarters

Kaseya Miami
701 Brickell Avenue
Suite 400
Miami, FL 33131
partners@datto.com
www.datto.com

Global Offices

USA: 888.294.6312
Canada: 877.811.0577
EMEA: +44 (0) 118 402 9606
Australia: +61 (02) 9696 8190
Singapore: +65-31586291

Copyright © 2023 Datto, Inc. All rights reserved. Effective June 2023.

All information accurate to the best of Datto's knowledge at the time prepared; Datto reserves the right to correct errors/discrepancies.